

Multistage Horizontal Centrifugal Pump

Type Series Booklet **DPHM(C)**



Legal information/Copyright

Type Series Booklet DPHM(C)

All rights reserved. The contents provided herein must neither be distributed, copied, reproduced, edited or processed for any other purpose, nor otherwise transmitted, published or made available to a third party without the manufacturer's express written consent.

Subject to technical modification without prior notice.

© Duijvelaar Pompen, Alphen aan den Rijn, Nederland 02/01/2017

Contents

Centrifugal Pumps	4
Multistage Horizontal Centrifugal Pumps	4
DPHM(C).....	4
Main applications	4
Fluids handled.....	4
Operating data	4
Designation	4
Design details	4
Materials	5
Product benefits	5
Certifications	5
Selection information	5
Minimum flow rate / maximum flow rate	5
Overview of product features / selection tables	6
Shaft seal.....	6
Technical data.....	7
DPHM, 1~230 V, 50 Hz	7
DPHM, 1~230 V, 60 Hz	7
DPHM, 230/400 V, 50 Hz	7
DPHM, 230/400 V, 60 Hz	8
DPHMC, 1~230 V, 50 Hz.....	8
DPHMC, 1~230 V, 60 Hz.....	9
DPHMC, 230/400 V, 50 Hz.....	9
DPHMC, 230/400 V, 60 Hz.....	9
Characteristic curves	11
n ≈ 2900 rpm.....	11
DPHM(C), 2, n ≈ 2900 rpm	11
DPHM(C), 4, n ≈ 2900 rpm	12
DPHM(C), 6, n ≈ 2900 rpm	13
n ≈ 3500 rpm.....	14
DPHM(C), 2, n ≈ 3500 rpm	14
DPHM(C), 4, n ≈ 3500 rpm	15
DPHM(C), 6, n ≈ 3500 rpm	16
Dimensions and connections	17
Dimensions	17
Connections	18
General assembly drawing with list of components	19

Centrifugal Pumps

Multistage Horizontal Centrifugal Pumps

DPHM(C)



Main applications

- Cold water pressure booster systems
- Cold water systems
- General irrigation systems
- Light industrial applications

Fluids handled

- Clean water (without solids)
- Slightly aggressive fluid

Operating data

Operating properties

Characteristic		Value
Flow rate	Q [m³/h]	≤ 10,8
Head	H [m]	≤ 79,5
Fluid temperature	T [°C]	-10 to +60
Ambient temperature	T [°C]	-20 to +40 ¹⁾
Pressure class	PN [bar]	10

¹⁾ Optional: -20 to +55 °C

Designation

Example: DPHMC 2/2

Designation key

Code	Description
DPHM	Type series
C	Material variant
C	Pump casing made of cast iron
-	Pump casing made of cast stainless steel
2	Size, flow rate [m³/h] at BEP
2, 4, 6	
2	Number of stages ²⁾

²⁾ Standard: 2, 4 and 6; optional: 1, 3 and 5 intermediate stages

Design details

Design

- Centrifugal pump
- Multistage
- Close-coupled design
- Extended motor shaft
- Maximum pressure class PN 10

Installation

- Horizontal installation

Drive

- Single-phase AC motor or three-phase motor
- To IEC 60034-7
- Efficiency class IE3 to IEC 60034-30 (for three-phase motors ≥ 0.75 kW)
- Frequency 50/60 Hz
- 2 poles
- Thermal class F
- IP55 enclosure
- Mode of operation: continuous operation S1
- Thermal circuit breaker with automatic reset and start-up for single-phase AC motor

Shaft seal

- Mechanical seal
- To EN 12756
- Uncooled
- Maintenance-free

Materials

Overview of materials depending on material variant

Part No.	Description	In contact with water	DPHM	DPHMC
10-6	Pump shroud	X	1.4301	
101	Pump casing	X	1.4308	EN-GJL-250
108.01/.04/.05	Stage casing	X	1.4301	
160	Cover	X	1.4301	
-	Shaft	X	1.4541	
230	Impeller	X	1.4301	
341	Drive lantern	-	EN-GJL-250	
412	O-ring	X	EPDM	
433	Mechanical seal	X	B V E F F	B V P F F
525.01/.03/.05	Spacer sleeve	X	1.4305	
903.05	Vent plug	X	1.4301 / EPDM	PEHD / TPE
905	Tie bolt	-	1.4057	
920.02/.03	Nut	X	1.4301	
930.02	Lock washer	X	1.4401	
932	Circlip	X	1.4571	
950	Spring	X	1.4401	

Comparison of materials

EN	General description	EN material code	EN standard	ASTM
EN-GJL-250	Cast iron	GJL-250	EN 1561	A48 - 40 B
1.4057	Chrome nickel steel	X17CrNi 16-2--QT800	EN 10088-3	A276 - 431
1.4301	Chrome nickel steel	X5CrNi 18-10	EN 10088	A276 - 304
1.4305	Chrome nickel steel	X8CrNiS 18-9	EN 10088	A276 - 303
1.4308	Chrome nickel steel	GX5CrNi19-10	EN 10213-4	A351 - Grade CF8
1.4401	Chrome nickel molybdenum steel	X5CrNiMo 17-12-2	EN 10088	A276 - 316
1.4541	Chrome nickel steel	X6CrNiMoTi 18-10	EN 10088	A276 - 321
1.4571	Chrome nickel molybdenum steel	X6CrNiMoTi 17-12-2	EN 10088	A276 - 316Ti

Product benefits

- Top quality pump thanks to advanced high-precision production technology and resistant high-grade materials
- An energy-saving, state-of-the-art pump solution characterised by high efficiency levels, optimum flow passage, the use of high-efficiency motors, and precision engineering of all hydraulic components
- High energy efficiency as well as low investment and maintenance costs make for low life cycle costs
- Very compact, space-saving design

Label	Effective in:	Comment
	United Kingdom	For material variant cast stainless steel

Selection information

Minimum flow rate / maximum flow rate

A minimum flow rate must be ensured to protect the pump against overheating and to prevent gas pockets, cavitation, etc.

Minimum flow rate / maximum flow rate Q [m³/h] at a fluid temperature ≤ 20 °C

Size	50 Hz		60 Hz	
	Min.	Max.	Min.	Max.
2	0,2	3,3	0,2	4,0
4	0,4	6,5	0,5	7,8
6	0,6	9,0	0,8	10,8

Certifications

Overview

Label	Effective in:	Comment
	France	For material variant cast stainless steel

Overview of product features / selection tables

Shaft seal

Mechanical seal material – DPHM

Code to EN 12756	Description	Material	Code	Comment
B	Primary ring	Carbon graphite	Ca	Resin-impregnated
V	Mating ring	Aluminium oxide	Ce	Ceramics
E	Elastomer	EPDM	EPDM	Ethylene propylene rubber ³⁾
F	Spring	Chrome nickel steel	CrNi steel	-
F	Other metal parts	Chrome nickel steel	CrNi steel	-

Mechanical seal material – DPHMC

Code to EN 12756	Description	Material	Code	Comment
B	Primary ring	Carbon graphite	Ca	Resin-impregnated
V	Mating ring	Aluminium oxide	Ce	Ceramics
P	Elastomer	NBR	NBR	Nitrile butadiene rubber
F	Spring	Chrome nickel steel	CrNi steel	-
F	Other metal parts	Chrome nickel steel	CrNi steel	-

³⁾ To ACS / WRAS

Technical data

DPHM, 1~230 V, 50 Hz

50 Hz

Size	n [rpm]	P _N [kW]	I _A /I _N	cos φ	V _N	η	L _p [dB]	Cable gland	Maximum frequency of starts [h ⁻¹]	I _N 1~230 V	Mat. No.	[kg]
					Tolerance [%]					[A]		
2/2	2750	0,37	3,70	0,92	+/-10	67,00	58,00	1 × M18 × 1,5	20	2,60	290029451020MX	13,1
2/4	2750	0,37	3,70	0,92	+/-10	67,00	58,00	1 × M18 × 1,5	20	2,60	290029451040MX	13,8
2/6	2760	0,55	3,90	0,92	+/-10	70,00	56,00	1 × M18 × 1,5	20	3,69	290029451060MX	15,9
4/2	2750	0,37	3,70	0,92	+/-10	67,00	58,00	1 × M18 × 1,5	20	2,60	290049451020MX	13,1
4/4	2760	0,55	3,90	0,92	+/-10	70,00	56,00	1 × M18 × 1,5	20	3,69	290049451040MX	15,3
4/6	2790	1,10	4,30	0,95	+/-10	75,00	58,00	1 × M20 × 1,5	20	6,68	290049451060MX	20
6/2	2750	0,37	3,70	0,92	+/-10	67,00	58,00	1 × M18 × 1,5	20	2,60	290069451020MX	13,4
6/4	2790	1,10	4,30	0,95	+/-10	75,00	58,00	1 × M20 × 1,5	20	6,68	290069451040MX	19,7
6/6	2800	1,50	4,80	0,95	+/-10	76,00	58,00	1 × M20 × 1,5	20	8,99	290069451060MX	23,1

DPHM, 1~230 V, 60 Hz

60 Hz

Size	n [rpm]	P _N [kW]	I _A /I _N	cos φ	V _N	η	L _p [dB]	Cable gland	Maximum frequency of starts [h ⁻¹]	I _N 1~230 V	Mat. No.	[kg]
					Tolerance [%]					[A]		
2/2	3450	0,37	4,50	0,95	+/-10	74,00	64,00	1 × M18 × 1,5	20	2,30	290029461020MX	13,1
2/4	3420	0,55	3,80	0,96	+/-10	74,00	65,00	1 × M18 × 1,5	20	3,35	290029461040MX	15,2
2/6	3420	0,75	4,30	0,97	+/-10	75,00	68,00	1 × M20 × 1,5	20	4,50	290029461060MX	17,4
4/2	3420	0,55	3,80	0,96	+/-10	74,00	65,00	1 × M18 × 1,5	20	3,35	290049461020MX	14,5
4/4	3400	1,10	4,80	0,96	+/-10	79,00	72,00	1 × M20 × 1,5	20	6,30	290049461040MX	19,3
4/6	3420	1,50	4,70	0,95	+/-10	76,00	75,00	1 × M20 × 1,5	20	9,10	290049461060MX	22,7
6/2	3420	0,75	4,30	0,97	+/-10	75,00	68,00	1 × M20 × 1,5	20	4,50	290069461020MX	16,3
6/4	3420	1,50	4,70	0,95	+/-10	76,00	75,00	1 × M20 × 1,5	20	9,10	290069461040MX	22,4
6/6	3420	2,20	4,50	0,95	+/-10	77,00	78,00	1 × M20 × 1,5	20	13,10	290069461060MX	25,1

DPHM, 230/400 V, 50 Hz

50 Hz

Size	n [rpm]	P _N [kW]	I _A /I _N	cos φ	U _N	η	L _p [dB]	Cable gland	Maximum frequency of starts [h ⁻¹]	I _N 230/400 V	Mat. No.	[kg]
					Tolerance [%]					[A]		
2/2	2750	0,37	4,60	0,78	+/-10	74,20	58,00	1 × M20 × 1,5	20	1,64/0,94	290029451020A	13,1
2/4	2750	0,37	4,60	0,78	+/-10	74,20	58,00	1 × M20 × 1,5	20	1,64/0,94	290029451040A	13,8

Size	n	P _N	I _A /I _N	cos φ	U _N	η	L _p	Cable gland	Maximum frequency of starts	I _N	Mat. No.	[kg]
	[rpm]	[kW]			Tolerance					230/400 V		
					[%]	[%]	[dB]		[h ⁻¹]	[A]		
2/6	2790	0,55	5,20	0,75	+/-10	77,60	58,00	1 × M20 × 1,5	20	2,31/1,33	290029451060A	15,9
4/2	2750	0,37	4,60	0,78	+/-10	74,20	58,00	1 × M20 × 1,5	20	1,64/0,94	290049451020A	13,1
4/4	2790	0,55	5,20	0,75	+/-10	77,60	58,00	1 × M20 × 1,5	20	2,31/1,33	290049451040A	15,3
4/6	2855	1,10	7,00	0,80	+/-10	82,70	60,00	2 × M20 × 1,5	25	4,22/2,43	290049451060U	20
6/2	2750	0,37	4,60	0,78	+/-10	74,20	58,00	1 × M20 × 1,5	20	1,64/0,94	290069451020A	13,4
6/4	2855	1,10	7,00	0,80	+/-10	82,70	60,00	2 × M20 × 1,5	25	4,22/2,43	290069451040U	19,7
6/6	2900	1,50	7,70	0,88	+/-10	84,20	63,00	2 × M25 × 1,5	25	5,08/2,92	290069451060U	23,1

DPHM, 230/400 V, 60 Hz

60 Hz

Size	n	P _N	I _A /I _N	cos φ	U _N	η	L _p	Cable gland	Maximum frequency of starts	I _N	Mat. No.	[kg]
					Tolerance					230/400 V		
	[rpm]	[kW]			[%]	[%]	[dB]		[h ⁻¹]	[A]		
2/2	3300	0,37	3,90	0,78	+20/-5	75,70	58,00	1 × M20 × 1,5	20	1,54/0,89	290029461020A	13,1
2/4	3345	0,55	4,40	0,75	+20/-5	77,60	56,00	1 × M20 × 1,5	20	2,29/1,32	290029461040A	15,2
2/6	3440	0,75	6,50	0,80	+20/-5	80,90	60,00	2 × M20 × 1,5	25	2,87/1,65	290029461060U	17,4
4/2	3345	0,55	4,40	0,75	+20/-5	77,60	56,00	1 × M20 × 1,5	20	2,29/1,32	290049461020A	14,5
4/4	3440	1,10	6,70	0,81	+20/-5	82,90	60,00	2 × M20 × 1,5	25	4,72/2,72	290049461040U	19,3
4/6	3500	1,50	6,70	0,89	+20/-5	84,4	66,00	2 × M25 × 1,5	25	5,01/2,88	290049461060U	22,7
6/2	3440	0,75	6,50	0,80	+20/-5	80,90	60,00	2 × M20 × 1,5	25	2,87/1,65	290069461020U	16,3
6/4	3500	1,50	6,70	0,89	+20/-5	84,4	66,00	2 × M25 × 1,5	25	5,01/2,88	290069461040U	22,4
6/6	3500	2,20	6,70	0,90	+20/-5	86,10	66,00	1 × M25 × 1,5	25	7,12/4,09	290069461060U	25,1

DPHMC, 1~230 V, 50 Hz

50 Hz

Size	n	P _N	I _A /I _N	cos φ	V _N	η	L _p	Cable gland	Maximum frequency of starts	I _N	Mat. No.	[kg]
					Tolerance					1~230 V		
	[rpm]	[kW]			[%]	[%]	[dB]		[h ⁻¹]	[A]		
2/2	2750	0,37	3,70	0,92	+/-10	67,00	58,00	1 × M18 × 1,5	20	2,60	290028451020MX	13,1
2/4	2750	0,37	3,70	0,92	+/-10	67,00	58,00	1 × M18 × 1,5	20	2,60	290028451040MX	13,8
2/6	2760	0,55	3,90	0,92	+/-10	70,00	56,00	1 × M18 × 1,5	20	3,69	290028451060MX	15,9
4/2	2750	0,37	3,70	0,92	+/-10	67,00	58,00	1 × M18 × 1,5	20	2,60	290048451020MX	13,1
4/4	2760	0,55	3,90	0,92	+/-10	70,00	56,00	1 × M18 × 1,5	20	3,69	290048451040MX	15,3
4/6	2790	1,10	4,30	0,95	+/-10	75,00	58,00	1 × M20 × 1,5	20	6,68	290048451060MX	20
6/2	2750	0,37	3,70	0,92	+/-10	67,00	58,00	1 × M18 × 1,5	20	2,60	290068451020MX	13,4
6/4	2790	1,10	4,30	0,95	+/-10	75,00	58,00	1 × M20 × 1,5	20	6,68	290068451040MX	19,7
6/6	2800	1,50	4,80	0,95	+/-10	76,00	58,00	1 × M20 × 1,5	20	8,99	290068451060MX	23,1

DPHMC, 1~230 V, 60 Hz

60 Hz

Size	n	P _N	I _A /I _N	cos φ	V _N	η	L _p	Cable gland	Maximum frequency of starts	I _N	Mat. No.	[kg]
	[rpm]	[kW]			Tolerance					1~230 V		
					[%]	[%]	[dB]		[h ⁻¹]	[A]		
2/2	3450	0,37	4,50	0,95	+/-10	74,00	64,00	1 × M18 × 1,5	20	2,30	290028461020MX	13,1
2/4	3420	0,55	3,80	0,96	+/-10	74,00	65,00	1 × M18 × 1,5	20	3,35	290028461040MX	15,2
2/6	3420	0,75	4,30	0,97	+/-10	75,00	68,00	1 × M20 × 1,5	20	4,50	290028461060MX	17,4
4/2	3420	0,55	3,80	0,96	+/-10	74,00	65,00	1 × M18 × 1,5	20	3,35	290048461020MX	14,5
4/4	3400	1,10	4,80	0,96	+/-10	79,00	72,00	1 × M20 × 1,5	20	6,30	290048461040MX	19,3
4/6	3420	1,50	4,70	0,95	+/-10	76,00	75,00	1 × M20 × 1,5	20	9,10	290048461060MX	22,7
6/2	3420	0,75	4,30	0,97	+/-10	75,00	68,00	1 × M20 × 1,5	20	4,50	290068461020MX	16,3
6/4	3420	1,50	4,70	0,95	+/-10	76,00	75,00	1 × M20 × 1,5	20	9,10	290068461040MX	22,4
6/6	3420	2,20	4,50	0,95	+/-10	77,00	78,00	1 × M20 × 1,5	20	13,10	290068461060MX	25,1

DPHMC, 230/400 V, 50 Hz

50 Hz

Size	n	P _N	I _A /I _N	cos φ	U _N	η	L _p	Cable gland	Maximum frequency of starts	I _N	Mat. No.	[kg]
					Tolerance					230/400 V		
	[rpm]	[kW]			[%]	[%]	[dB]		[h ⁻¹]	[A]		
2/2	2750	0,37	4,60	0,78	+/-10	74,20	58,00	1 × M20 × 1,5	20	1,64/0,94	290028451020A	13,1
2/4	2750	0,37	4,60	0,78	+/-10	74,20	58,00	1 × M20 × 1,5	20	1,64/0,94	290028451040A	13,8
2/6	2790	0,55	5,20	0,75	+/-10	77,60	58,00	1 × M20 × 1,5	20	2,31/1,33	290028451060A	15,9
4/2	2750	0,37	4,60	0,78	+/-10	74,20	58,00	1 × M20 × 1,5	20	1,64/0,94	290048451020A	13,1
4/4	2790	0,55	5,20	0,75	+/-10	77,60	58,00	1 × M20 × 1,5	20	2,31/1,33	290048451040A	15,3
4/6	2855	1,10	7,00	0,80	+/-10	82,70	60,00	2 × M20 × 1,5	25	4,22/2,43	290048451060U	20
6/2	2750	0,37	4,60	0,78	+/-10	74,20	58,00	1 × M20 × 1,5	20	1,64/0,94	290068451020A	13,4
6/4	2855	1,10	7,00	0,80	+/-10	82,70	60,00	2 × M20 × 1,5	25	4,22/2,43	290068451040U	19,7
6/6	2900	1,50	7,70	0,88	+/-10	84,20	63,00	2 × M25 × 1,5	25	5,08/2,92	290068451060U	23,1

DPHMC, 230/400 V, 60 Hz

60 Hz


Size	n	P _N	I _A /I _N	cos φ	U _N	η	L _p	Cable gland	Maximum frequency of starts	I _N	Mat. No.	[kg]
					Tolerance					230/400 V		
	[rpm]	[kW]			[%]	[%]	[dB]		[h ⁻¹]	[A]		
2/2	3300	0,37	3,90	0,78	+20/-5	75,70	58,00	1 × M20 × 1,5	20	1,54/0,89	290028461020A	13,1
2/4	3345	0,55	4,40	0,75	+20/-5	77,60	56,00	1 × M20 × 1,5	20	2,29/1,32	290028461040A	15,2
2/6	3440	0,75	6,50	0,80	+20/-5	80,90	60,00	2 × M20 × 1,5	25	2,87/1,65	290028461060U	17,4

Size	n	P _N	I _A /I _N	cos φ	U _N	η	L _p	Cable gland	Maximum frequency of starts	I _N	Mat. No.	[kg]
					Tolerance					230/400 V		
	[rpm]	[kW]			[%]	[%]	[dB]		[h ⁻¹]	[A]		
4/2	3345	0,55	4,40	0,75	+20/-5	77,60	56,00	1 × M20 × 1,5	20	2,29/1,32	290048461020A	14,5
4/4	3440	1,10	6,70	0,81	+20/-5	82,90	60,00	2 × M20 × 1,5	25	4,72/2,72	290048461040U	19,3
4/6	3500	1,50	6,70	0,89	+20/-5	84,4	66,00	2 × M25 × 1,5	25	5,01/2,88	290048461060U	22,7
6/2	3440	0,75	6,50	0,80	+20/-5	80,90	60,00	2 × M20 × 1,5	25	2,87/1,65	290068461020U	16,3
6/4	3500	1,50	6,70	0,89	+20/-5	84,4	66,00	2 × M25 × 1,5	25	5,01/2,88	290068461040U	22,4
6/6	3500	2,20	6,70	0,90	+20/-5	86,10	66,00	1 × M25 × 1,5	25	7,12/4,09	290068461060U	25,1

Characteristic curves


$n \approx 2900$ rpm

DPHM(C), 2, $n \approx 2900$ rpm




St = 1 | P per stage

DPHM(C), 4, $n \approx 2900$ rpm



St = 1 | P per stage


DPHM(C), 6, $n \approx 2900$ rpm



St = 1 | P per stage


$n \approx 3500$ rpm

DPHM(C), 2, $n \approx 3500$ rpm




St = 1 | P per stage

DPHM(C), 4, $n \approx 3500$ rpm



St = 1 | P per stage

DPHM(C), 6, $n \approx 3500$ rpm



St = 1 | P per stage

Dimensions and connections

Dimensions




Fig. 1: Dimensions [mm]

Dimensions, 1~230 V, 50 Hz

Size	P _N [kW]	E1 [mm]	E2 [mm]	F1 [mm]	F2 [mm]
2/2	0,37	138,50	110,00	372,50	151,50
2/4	0,37	138,50	110,00	405,00	184,00
2/6	0,55	138,50	110,00	448,00	227,00
4/2	0,37	138,50	110,00	372,50	151,50
4/4	0,55	138,50	110,00	405,00	184,00
4/6	1,10	159,00	155,00	473,00	227,00
6/2	0,37	138,50	110,00	372,50	151,50
6/4	1,10	159,00	155,00	440,50	194,50
6/6	1,50	176,50	160,00	529,50	244,50

Dimensions, 1~230 V, 60 Hz

Size	P _N [kW]	E1 [mm]	E2 [mm]	F1 [mm]	F2 [mm]
2/2	0,37	138,50	110,00	372,50	151,50
2/4	0,55	138,50	110,00	405,00	184,00
2/6	0,75	159,00	155,00	473,00	227,00
4/2	0,55	138,50	110,00	372,50	151,50
4/4	1,10	159,00	155,00	430,00	184,00
4/6	1,50	176,50	160,00	512,00	227,00
6/2	0,75	159,00	155,00	397,50	151,50
6/4	1,50	176,50	160,00	479,50	194,50
6/6	2,20	176,50	160,00	529,50	244,50

Dimensions, 230/400 V, 50 Hz

Size	P _N [kW]	E1 [mm]	E2 [mm]	F1 [mm]	F2 [mm]
2/2	0,37	138,00	109,00	372,50	151,50
2/4	0,37	138,00	109,00	405,00	184,00
2/6	0,55	138,00	109,00	448,00	227,00
4/2	0,37	138,00	109,00	372,50	151,50
4/4	0,55	138,00	109,00	405,00	184,00
4/6	1,10	157,00	133,00	487,00	227,00
6/2	0,37	138,00	109,00	372,50	151,50

Size	P _N	E1	E2	F1	F2
	[kW]	[mm]	[mm]	[mm]	[mm]
6/4	1,10	157,00	133,00	454,50	194,50
6/6	1,50	180,00	145,00	497,50	244,50

Dimensions, 230/400 V, 60 Hz

Size	P _N	E1	E2	F1	F2
	[kW]	[mm]	[mm]	[mm]	[mm]
2/2	0,37	138,00	109,00	372,50	151,50
2/4	0,55	138,00	109,00	405,00	184,00
2/6	0,75	157,00	133,00	484,00	227,00
4/2	0,55	138,00	109,00	372,50	151,50
4/4	1,10	157,00	133,00	444,00	184,00
4/6	1,50	180,00	145,00	480,00	227,00
6/2	0,75	157,00	133,00	408,50	151,50
6/4	1,50	180,00	145,00	447,50	194,50
6/6	2,20	180,00	145,00	529,50	244,50

Connections




Fig. 2: Connections

A	Discharge nozzle (G 1), internal thread	C	Suction nozzle (G 1 1/4), internal thread
B	Screw filler plug (G 1/4)	D	Screw drain plug (G 1/4)

General assembly drawing with list of components




Fig. 3: General assembly drawing

List of components

Part No.	Description	Part No.	Description
10-6	Pump shroud	554.01	Washer
101	Pump casing	580.02	Cap
108.01/.04/.05	Stage casing	800	Motor
160	Cover	903.05	Screw plug
230	Impeller	905	Tie bolt
341	Drive lantern	914.02	Hexagon socket head cap screw
400.04	Gasket	920.02/.03	Nut
412.01/.03	O-ring	930.02	Safety device
433	Mechanical seal	932	Circlip
525.01/.03/.05	Spacer sleeve	950	Spring

dp pumps

P.O. Box 28
2400 AA Alphen aan den Rijn
The Netherlands

t +31 172 48 83 88
f +31 172 46 89 30

dp@dp-pumps.com
www.dp-pumps.com

02.01.2017

97007104 (1799.560/05.EN)

